

### **Amendments to the Claims:**

Please replace claims 2, 5-6, 10-12, 16-17, 20, 23, 25-27, 29 and 31 as shown below. Please cancel claim 28. Claims 2, 3 and 4 are original patent claims and they are presented as amended relative to the original patent specification in claims, including bracketing and underlining as set forth in 37 C.F.R. § 1.173(d)(1) and (2) and MPEP § 1453. Claims 5-6, 10-12, 16-17, 20, 23, 25-27, 29 and 31 are new claims (i.e., claims not found in the patent, that were previously presented in the reissue application) and thus are represented “containing the amendatory material, and completely underlining the claim.” MPEP § 1453. Accordingly, the changes are pointed out in the “Remarks” portion of the amendment and the support for these changes is explained. 37 C.F.R. § 1.173(c) and MPEP § 1453.

2. (Currently Amended) A sliding sun visor assembly comprising:  
a rod assembly including a longitudinally extending rod, a torque control  
pivotally attached to said rod, and a guide fixed to one surface of said torque control, said  
guide having a substantially H-shaped cross section; and  
a visor body including a longitudinally extending bore for receiving said rod,  
and a longitudinally extending track, said track forming a substantially enclosed longitudinally  
extending passage adjacent one surface of said visor body, said passage being shaped to receive  
a portion of said guide in a sliding engagement; whereby upon moving the visor body  
longitudinally along said rod, said track slides relative to said guide;

[The sliding visor assembly of claim 1,] wherein said track includes a first [vertical] wall extending perpendicularly from said surface of said visor body; a second [vertical] wall extending perpendicularly from said surface of the visor body, said second [vertical] wall being spaced from said first [vertical] wall; and a [horizontal] third wall substantially parallel to said surface of the visor body, said [horizontal] third wall extending between the first and second walls and being spaced from said surface of said visor body such that said passage is formed therebetween, said [horizontal] third wall including a partially longitudinally extending slot.

3. (Previously Amended) A sliding sun visor assembly comprising:  
a rod assembly including a longitudinally extending rod, a torque control pivotally attached to said rod, and a guide fixed to one surface of said torque control and;  
a visor body including a longitudinally extending bore for receiving said rod, and a longitudinally extending track, said track forming a substantially enclosed longitudinally extending passage adjacent one surface of said visor body, said passage being shaped to receive a portion of the guide in a sliding engagement whereby upon moving said visor body longitudinally along said rod, said track slides relative to said guide, said track further including a first [vertical] wall extending from , and perpendicular to said surface of said visor body, a second [vertical] wall extending from , and perpendicular to said surface of said visor body, said second [vertical] wall being spaced from , and parallel to said first [vertical] wall, and a [horizontal] third wall substantially parallel to said surface of said visor body, said

[horizontal] third wall extending between said first and second walls and being spaced from said surface of said visor body such that said passage is formed therebetween, said [horizontal] third wall including a partially longitudinally extending slot.

4. (Previously Amended) A sliding sun visor assembly comprising:  
a rod assembly including a longitudinally extending rod, a torque control pivotally attached to said rod, and a guide fixed to one surface of said torque control; and  
a visor body including a longitudinally extending bore for receiving said rod, and a longitudinally extending track, said track forming a substantially enclosed longitudinally extending passage adjacent one surface of the visor body, said passage being shaped to receive a portion of the guide in a sliding engagement whereby upon moving said body longitudinally along said rod, said track slides relative to said guide, said guide further including a first leg coupled to said torque [controls] control, a second leg, and a cross bar joining said first leg to said second leg, such that said legs are spaced and parallel to one another, wherein upon assembly said second leg is received within said passage and said cross bar extends through a slot formed within said track.

5. A sliding sun visor assembly comprising:  
a rod assembly including:  
a longitudinally extending rod;  
a torque control pivotally attached to said rod, and a guide fixed to one surface of said torque control, the guide having a pair of opposing legs defining a longitudinal slot therebetween; and  
a visor body including:  
a structure projecting therefrom defining a longitudinally extending bore for receiving said rod, and  
a longitudinally extending track being shaped to receive a portion of said guide, wherein the track cooperates longitudinally between the pair of opposing legs of said guide in a sliding engagement within the slot, whereby upon moving the visor body longitudinally along said rod, said track slides relative to said guide.

6. The visor of claim 5, wherein the structure projecting from the visor body at least partially circumscribes said rod and defines a second pivotal attachment to said rod, wherein at least one of said pivotal attachments is slidably engaged to said rod, and said second pivotal attachment is slidably engaged with said rod.

10. The visor of claim 8, wherein the pair of opposing legs slidably receive said wall that projects from said visor body therebetween.

11. The visor of claim 8, wherein a ridge extends from said wall of said track of said visor body.

12. The visor of claim 5, wherein said track forms a substantially enclosed longitudinally extending passage adjacent one surface of said visor body, and said visor is assembled by sliding the opposing legs of said guide onto said track from an opening to the passage provided on a distal end of said track.

16. A sliding sun visor comprising:  
a rod assembly including a longitudinally extending rod, a torque control pivotally attached to said rod, and a guide fixed to one surface of said torque control, the guide having a pair of laterally spaced opposing legs; and

a visor body including a longitudinally extending bore for receiving said rod, the bore being substantially coaxial with the rod, and the visor body including a longitudinally extending track, one of said track and said pair of opposing legs of said guide forming a substantially enclosed longitudinally extending passage adjacent one surface of said visor body, said passage being shaped to receive a portion of the other of said track and said pair of opposing legs of said guide in a sliding engagement; whereby upon moving the visor body longitudinally along said rod, said track slides relative to said guide.

17. The visor of claim 16, wherein said bore is slidably engaged with the rod, and said torque control is non-slidably engaged with the rod.

20. The visor of claim 16, wherein the guide has a U-shaped lowermost portion extending therefrom for cooperating with said track.

23. The visor of claim 16, wherein the track includes a projection adapted to be received between said legs for sliding engagement therewith.

25. The visor of claim 16, wherein said track forms said passage, and said visor is assembled by sliding the opposing legs of said guide onto said track from a distal end of said track.

26. The visor of claim 16, wherein a portion of said visor body proximate to said longitudinally extending bore limits a longitudinal range of movement of said visor body along said rod by contacting the torque control.

27. The visor of claim 26, wherein the portion of said visor body proximate to said longitudinally extending bore includes a projection to assist in limiting said longitudinal range of movement of said visor body along said rod by contacting the torque control.

29. A sliding sun visor comprising:  
a rod assembly including a longitudinally extending rod, a torque control pivotally attached to said rod, said first pivotal attachment being substantially coaxial with said longitudinal rod, and a guide fixed to and extending from one surface of said torque control, said guide including a pair of opposing legs extending therefrom defining a longitudinal slot therebetween; and

a visor body including a longitudinally extending bore for receiving said rod allowing said visor body to slide axially with respect to said rod, said longitudinally extending bore being substantially coaxial with said rod; said visor body also including a longitudinally extending track slidably engaged between said opposing legs of said guide and received within said longitudinal slot, said track forming a substantially enclosed longitudinally extending passage adjacent one surface of said visor body, said passage being shaped to receive a portion

of said guide in a sliding engagement; whereby upon moving the visor body longitudinally along said rod, said track slides relative to said guide.

31. A sun visor assembly comprising:

a rod assembly including a longitudinally extending rod having an elbow formed therein, a torque control pivotally attached to said rod in a non-slidable manner, and a guide fixed to one surface of said torque control and including a pair of opposing legs extending therefrom; and

a visor body including a longitudinally extending bore for receiving said rod, said bore slidable along said rod between said torque control and said elbow, and a longitudinally extending track, said pair of opposing legs of said guide forming a substantially enclosed longitudinally extending passage adjacent one surface of said visor body, said passage being shaped to receive a portion of said track in a sliding engagement; whereby upon moving the visor body longitudinally along said rod, said track slides relative to said guide.